

P&T SpectraGuard™ Vinyl Series 2300 Energy Performance

SELECT FROM THE BLUE SHADED OPTIONS BELOW THAT QUALIFY FOR THE 2009-2010 ENERGY TAX CREDIT

The American Recovery and Reinvestment Act of 2009 (ARRA)

SpectraGuard Series 2300			Standard Energy Package PPG Solarban® 60 Low-E and argon filled Super Spacer® NXT			Climate Control Package PPG Solarban® 70XL Low-E and argon filled Super Spacer® NXT			Sound & Security Package PPG Solarban® 70XL Low-E and argon filled Super Spacer® NXT	
			No Grids	GBG/SDL Grids	Contour Grids	No Grids	GBG/SDL Grids	Contour Grids	No Grids	GBG/SDL Grids
Size	DP	Energy Criteria	Performance			Performance			Performance	
Double Hung 2360*										
48" x 68"	45	U-Factor	.30	.30	.30	.29	.29	.29	.30	.31
44" x 75"	30	Solar Heat Gain Coefficient (SHGC)	.29	.26	.26	.21	.19	.19	.21	.19
44" x 62"	50	Visible Light Transmittance (VT)	.53	.47	.47	.47	.42	.42	.46	.40
36" x 75"	40	2010 Energy Star® Zone	2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3
48" x 86"	50	U-Factor	.33	.33	.33	.31	.31	.31	.32	.33
		Solar Heat Gain Coefficient (SHGC)	.29	.26	.26	.21	.19	.19	.21	.19
54" x 91"	35	Visible Light Transmittance (VT)	.53	.47	.47	.47	.42	.42	.46	.40
		2010 Energy Star® Zone	2	1, 2	1, 2	1, 2, 3	1, 2, 3	1, 2, 3	1, 2, 3	1, 2
Horizontal Roller 2310*										
72" x 60" - XX	35	U-Factor	.29	.29	.29	.28	.28	.28	.29	.30
72" x 54" - XX	50	Solar Heat Gain Coefficient (SHGC)	.30	.27	.27	.21	.19	.19	.21	.19
108" x 60" - XOX	35	Visible Light Transmittance (VT)	.55	.49	.49	.49	.43	.43	.47	.42
108" x 54" - XOX	50	2010 Energy Star® Zone	2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4
Picture/Architectural 2320										
Units up to 25 sq. ft.	50	U-Factor	.28	.28	.28	.28	.28	.28	.28	.29
		Solar Heat Gain Coefficient (SHGC)	.34	.30	.30	.24	.22	.22	.24	.22
		Visible Light Transmittance (VT)	.62	.55	.55	.55	.49	.49	.53	.48
		2010 Energy Star® Zone	3, 4	2, 3, 4	2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4
Units over 25 sq. ft.	50	U-Factor	.28	.28	.32	.28	.27	.30	N/A	
		Solar Heat Gain Coefficient (SHGC)	.33	.30	.30	.24	.22	.22		
		Visible Light Transmittance (VT)	.61	.54	.54	.54	.48	.48		
		2010 Energy Star® Zone	3, 4	2, 3, 4	2, 3	1, 2, 3, 4	1, 2, 3, 4	1, 2, 3, 4		

Note: A tempered glass upgrade may be required to achieve certain sizes that meet the Energy Tax Credit.

* Some sizes and configurations may not qualify for the Energy Tax Credit. Please utilize our WebWeaver™ entry system for eligible configurations.

STANDARD ENERGY PACKAGE

- General purpose, energy efficient option
- Can be used in most climate or home heating / cooling situations

CLIMATE CONTROL PACKAGE

- Customized to meet any climate and home heating / cooling situations
- Exceptional U-Factor and Solar Heat Gain results (see chart)

SOUND & SECURITY PACKAGE

- Can be used in many climate or home heating / cooling situations
- Designed to provide an advanced level of sound reduction and security protection